



## 70" Extended Length Engineering Drawing

Container	7019	7025	7034	7041	7050
<b>External Dimensions</b>					
1	70	70	70	70	70
2	48	48	48	48	48
3	19	25	34	41	50
<b>Internal Dimensions</b>					
4	13.1	18.8	27.9	34.9	44
5	12.1	17.9	26.9	34	43
6	66.4	66.4	66.4	66.4	66.4
7	44.5	44.5	44.5	44.5	44.5
<b>Fork Tunnel Dimensions</b>					
8	33.5	33.5	33.5	33.5	33.5
9	12.1	12.1	12.1	12.1	12.1
10	9.4	9.4	9.4	9.4	9.4
11	3.5	3.5	3.5	3.5	3.5
12	33.6	33.6	33.6	33.6	33.6
13	12.1	12.1	12.1	12.1	12.1
14	9.4	9.4	9.4	9.4	9.4
<b>Stack Interlock</b>					
15	0.8	0.8	0.8	0.8	0.8
<b>Sidewall Height</b>					
16	6.8	6.8	6.8	6.8	6.8
17	N/A	N/A	N/A	22.8	22.8
<b>Sidewall Opening</b>					
18	N/A	N/A	50.7	N/A	50.7
19	N/A	N/A	35	N/A	35
<b>Drop Door Dimensions</b>					
A	N/A	33	32.2	33	32.2
B	N/A	12	16.2	12	21
C	N/A	7.1	11.5	23	23

(Units in inches)

Rigid load: Part is rigid across length and spans a minimum of 54" (64.5" container) or 60" (70" container).  
 Distributed load: All other unsupported loads.

All dimensions and specifications are approximate. Interior height dimensions measured from center; variances may result due to center crown. Tare weight is based on the 2-drop-door black model, and will vary based on color and configuration. Performance characteristics are based on uniform static loads and may be affected by concentrated loads and elevated temperatures.

Materials and workmanship guaranteed for 3 years. Material: HDPE.