

ROPAK

65" Ext. Length



ROPAK™ 65" Extended Length Containers are perfect for:

- Automotive Components
- Body Side Moldings
- Carpet
- Drive Shafts
- Exterior Trim
- Headlights
- Interior Trim

Container Model		6519	6525	6533	6534	6542	6550
Exterior Dimensions	length	64.5"/1638 mm	64.5"/1638 mm	64.5"/1638 mm	64.5"/1638 mm	64.5"/1638 mm	64.5"/1638 mm
	width	48"/1219 mm	48"/1219 mm	48"/1219 mm	48"/1219 mm	48"/1219 mm	48"/1219 mm
	height	19"/483 mm	25"/635 mm	33"/838 mm	34"/864 mm	42"/1067 mm	50"/1270 mm
Interior Dimensions	length	61.3"/1557 mm	61.3"/1557 mm	61.3"/1557 mm	61.3"/1557 mm	61.3"/1557 mm	61.3"/1557 mm
	width	44.8"/1138 mm	44.8"/1138 mm	44.8"/1138 mm	44.8"/1138 mm	44.8"/1138 mm	44.8"/1138 mm
	height	12.8"/325 mm	18.8"/477 mm	26.8"/681 mm	27.8"/706 mm	35.8"/909 mm	43.8"/1112 mm
	height to fill line	11.8"/300 mm	17.8"/452 mm	25.8"/655 mm	26.8"/681 mm	34.8"/884 mm	42.8"/1087 mm
Drop Door Options		0	0,1,2,3,4	0,1,2,3,4	0,1,2,3,4	0,1,2,3,4	0,1,2,3,4
Container Capacity		2000 lb/907 kg	2000 lb/907 kg	2000 lb/907 kg	2000 lb/907 kg	2000 lb/907 kg	2000 lb/907 kg
Stack Height	Static/Dynamic	5/4	5/4	5/2	5/2	4/2	4/2
Tare Weight (may vary)		142.2 lb/64.5 kg	180.1 lb/81.7 kg	204.2 lb/92.6 kg	209.2 lb/94.9 kg	232.3 lb/105.4 kg	251.7 lb/114 kg
Collapsed Height		N/A	12.9"/328 mm	12.9"/328 mm	12.9"/328 mm	22.1"/561 mm	22.1"/561 mm
Return Ratio		1:1	1.9:1	2.6:1	2.6:1	1.9:1	2.3:1
Drop Door Height	48" side	N/A	9.6"/244 mm	16"/406 mm	17"/432 mm	16"/406 mm	16"/406 mm
Drop Door Height	65" side	N/A	12.8"/325 mm	16"/406 mm	17"/432 mm	20.8"/528 mm	24"/610 mm
Truckload Qty (Closed)	48'/53'	80/90	128/144	128/144	128/144	48/54	48/54
Truckload Qty (Open)	48'/53'	80/90	64/72	48/54	48/54	32/36	32/36
40' ISO Cont. (Closed)	Std./Hi Cube	36/45	63/72	63/72	63/72	27/27	27/27
40' ISO Cont. (Open)	Std./Hi Cube	36/45	27/36	18/27	18/27	18/18	9/18
Standard Color		Black	Black	Black	Black	Black	Black

All dimensions and specifications are approximate. Tare weight is based on the 2-drop door black model and will vary based on color and configuration. Performance characteristics are based on uniform static loads and may be affected by concentrated loads and elevated temperatures.

Materials and workmanship guaranteed for 3 years. Material: HDPE

ROPAK

www.RopakReusableContainers.com 704-752-7944